

**General description**

The Rubber Rails with or without bolt sets is a recycled rubber molded block, ideal for supporting all vibrating equipment.

Molded aluminium rail (41 x 21 mm) suitable for M10 fasteners. Recommended temperature -30°C / +80°C.



- 4 preformed holes facilitating the mechanic fixation to the roof
- Excellent spread of load
- Preserves the waterproofing membrane of the roof
- Antivibration, U.V. resistant

**Technical specification**

<b>RBR* 2 V-RBR*</b>	<b>Height (mm)</b>	<b>Width (mm)</b>	<b>Length (mm)</b>	<b>Maximum recommended load (Kg)</b>
<b>50-250</b>	50	140	250	100
<b>50-400</b>	50	140	400	150
<b>95-250</b>	95	190	250	100
<b>95-400</b>	95	190	400	200
<b>95-600</b>	95	190	600	300
<b>95-800</b>	95	190	800	400
<b>95-1000</b>	95	190	1000	500

\*RBR : Rubber Rails are supplied by the unit without bolt sets

\*2 V-RBR : Rubber Rails are supplied by pair with 2 bolt sets  
(Bolt sets = 2 rail screw M10 x 30 mm + 2 nuts + 2 washers)

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.